

Camera G4 PTZ





Mechanical

| Dimensions | 207 x 223.7 x 341.3 mm (8.15 x 8.81 x 13.44") |
|---------------------|---|
| Weight | Without mount: 3.8 kg (8.38 lb) With mount: 6.8 kg (14.99 lb) |
| Enclosure materials | Metal, plastic |
| Mount material | Metal |
| Weatherproofing | IP66 |

Optics

| Sensor | Sony 4K (8 MP) 1/1.8" CMOS sensor |
|------------|--|
| Lens | 22x optical zoom |
| View angle | H: 3 to 64° V: 2 to 37° |
| Night mode | Built-in IR LED illumination and IR cut filter |

Video

| Video compression | H.264 |
|--------------------|--------------------|
| Resolution | 4K2K (3840 x 2160) |
| Maximum frame rate | 24 FPS |

System

| Processor specs | Ambarella S5L66 |
|-------------------------|------------------------------|
| Memory information | 1GB |
| Networking interface | 10/100/1,000 MbE RJ45 |
| Flash memory support | 256 MB |
| Max. power consumption | 42.9W |
| Power method | PoE++ |
| Supported voltage range | 42.5 ~ 57V |
| Button | Factory-reset |
| Mounting | Wall mount (Kit Included) |
| Operating temperature | -40 to 50° C (-40 to 122° F) |
| Operating humidity | 0 to 90% noncondensing |
| Certifications | FCC, IC, CE |

Software

| UniFi OS application | UniFi Protect |
|----------------------|-------------------------------|
| Mobile apps | UniFi Protect iOS and Android |

