

AVOCOR G SERIES DATASHEET

65" | 75" | 85"



OVERVIEW

The Avocor G series is a range of sleek, bezel-less, edge-to-edge interactive displays designed to streamline workplace collaboration. These crystalclear 4K collaboration displays use the latest InGlass[™] technology combined with bonded glass to deliver ultra-fast touch performance, supporting up to 20 individual touch points and 4 passive styluses. The result is a pixel-perfect user experience and high performance.

Available in stunning 65", 75", and 85" sizes, the G series collaboration displays give users an intuitive and interactive experience for participants in the room and meeting equity for those who are remote.

SOLUTION Highlights

> Single Type-C connectivity delivering audio, video, touch, Ethernet and power.

UiQ

Avocor UiQ - smart touch enabled dynamic user interface.

Zero parallax optically bonded glass surface for pixel-perfect inking.

Wake-on-presence sensons start-up the display when movement is detected.



 (\mathbf{O})

InGlass technology supporting palm rejection and 4 passive styluses.



40W crystal-clear audio experience with built-in active microphones.



IDEAL FOR:





Executive offices





DISPLAY	AVG-6560	AVG-7560	AVG-8560
Diagonal size (inch)	65	75	85
acklight		Direct-lit LED	
spect ratio		16:9	
lesolution		3840 x 2160 @ 60Hz	
Response time	9.5 ms		
Brightness	500 (cd/m2)		
Contrast ratio	5000:1		
/iewing angle	178°/178°		
Supported colors	30-bit deep color		
Display orientation		Landscape	
OUCH SYSTEM			
nterface	3 x USB-B 3.0		
ouch	Up to 20 point Avocor InGlass™ M5 Intelligent Touch - supports 4 x fine tip styluses - palm rest and palm rejection		
Glass	Zero parallax, bonded, anti-glare, anti-fingerprint		
Supported operating system	Windows 8 / 10, Mac OSX*, Linux*		
CONNECTIVITY			
ide inputs	1 x Type-C (60W PD) 2 x HDMI 20 2 x	USB-B 3 0 touch 1 x DisplayPort 1 2 1	x USB-B 3 0 touch 4 x USB-A hub 3
	1 x Type-C (60W PD), 2 x HDMI 2.0, 2 x USB-B 3.0 touch, 1 x DisplayPort 1.2, 1 x USB-B 3.0 touch, 4 x USB-A hub 1 x USB-A service port, HDMI Out		
op inputs		1x USB-A hub 3.0	
Nudio	1 x 3.5mm audio out, 1 x optical (SPDIF)		
Control	1 x IR input, 1 x RS-232, 1 x LAN Ethernet (RJ-45) in, 1 x LAN Ethernet (RJ-45) out		
DPS slot	Yes, 3840 x 2160 @60Hz		
AUDIO & MICROPHONE		-	
		1 x 10W - spatial-stored rear facing	
Built-in speakers	4 x 10W - spatial-stereo rear facing 4 x far-field, beam-forming - max 5m range		
Microphone array	4 x far-held, beam-forming - max 5m range Yes, max 3.5 range		
Presence sensor		res, max 3.5 range	
DISPLAY & REMOTE FUNCTIONS			
Auto-source- detection	Yes		
Source preview	Yes		
mage settings	5 x user / vivid / cinema / game / sports		
PHYSICAL SPECIFICATIONS			
Product dimensions	1481.4 x 884.4 x 116 mm 58.32 x 34.82 x 4.57 in	1703.5 x 1009.2 x 116.8 mm 67.07 x 39.73 x 4.6 in	1929.5 x 1138.5 x 117.2 mm 75.96 x 44.82 x 4.61 in
hipping dimensions	1672 x 1156 x 253 mm	2012 x 1294 x 284 mm	2160 x 1440 x 286 mm
Moight	65.83 x 45.51 x 9.96 in	79.21 x 50.94 x 11.18 in	85.04 x 56.69 x 11.26 in
Veight	Net: 56 kgs 123.46 lbs Gross: 75.55 kgs 164.45 lbs	Net: 71.6 kgs 157.85 lbs Gross: 100 kgs 220.46 lbs	Net: 91.3 kgs 201.28 lbs Gross: 124 kgs 273.37 lbs
Vall mount (VESA)	400 x 400 mm 15.75 x 15.75 in	600 x 400 mm	e ,
PC mount	100 x 100 mm 3.94 x 3.94 in		
Handles	4 x removable		
POWER			
Power supply	AC100-240V (worldwide), 50/60Hz		
AC power out	C14 to region-specific <335W <395W <480W		
Max power consumption	<33200		<480VV
itandby		≤0.5W	
INVIRONMENTAL			
Dperating temperature	0°C ~ 40°C		
itorage temperature	-20°C ~ 60°C		
lumidity	20% ~ 85%		
VHAT COMES IN THE BOX			
	1 x Remote control & batteries. 2 x 3mm	fine-tip passive touch styluses. AC powe	r cords (1 x UK, 1 x EU, 1 x US, 1 × Al
	1 x Remote control & batteries, 2 x 3mm 1 x USB-B 3.0 cable (3m 118.1 in), 1 x T	ype-C cable (1.8m 70.9 in), 1 x HDMI ca	able (3m 118.1 in), 1 x quick start gui
WARRANTY			

www.avocor.com

GroupShare Extended warranty

Avocor OPS

Austere Clean & Additional remote Additional stylus Protect

avocor

Details are subject to change without notice. All other logos and trademarks acknowledged. E&OE. *Please note up to 20-point touch in PC mode with Windows 7/8/10, MacOSX and Linux only supports single touch. Version: 09/20/2022